

*Probes*  
**Fiber to USB  
Converter**

Model HI-4413USB

**FEATURES:**

- **Connect to Any Computer USB Port**
- **Operational With ETS-Lindgren Battery Powered Probe Series:**
  - HI-44xx EMC Field Probes
  - HI-60xx EMC Field Probes
  - HI-3702 and HI-3638 Health and Safety Probes
- **No External Power Supply**
- **Includes ProbeView™ LT and USB Drivers Download**
- **Fully Compatible with ProbeView II**



*ETS-Lindgren's Model HI-4413USB Fiber to USB Converter*

**The HI-4413USB Fiber to USB Converter** is an economical way to collect and display data from all of the ETS-Lindgren EMC optically coupled field probes.

Connecting to the USB port of a personal computer, the HI-4413USB provides the interface with power directly from the USB port, so no external power supply is required.

ProbeView LT software (available for download from our website) provides a simple tool for collecting data and storing the field values on a personal computer.

ProbeView II is available at additional cost and provides real-time display, logging and analysis functions of EMF data. It can display a variety of test information, both numerically and graphically. A field intensity versus time chart is on the main screen along with the maximum field, X, Y, Z, and RMS values in addition to a variety of data logging options.

**STANDARD CONFIGURATION**

- HI-4413USB Converter
- USB to Mini-B Cable
- Downloadable ProbeView LT Software
- Downloadable USB Driver

**Physical Specifications**

MODEL	LENGTH	WIDTH/DIAMETER	HEIGHT
HI-4413USB	5.72 cm 2.25 in	3.18 cm 1.25 in	1.91 cm .75 in