

## Features

- ATEX/IEC intrinsically safe
- Measure or source 0 to 24 mA
- Accuracy 0.015% of reading
- Dual mA and % readout, linear or flow
- Step, span check, valve check, ramp
- 50 VDC measurement and continuity
- Hart® compatible

The UPS III IS is a rugged and extremely compact loop calibrator. Measuring 3.5 in x 5.5 in x 1.7 in (90 mm x 140 mm x 42 mm) and weighing just 16.2 oz (460 g). It is an essential tool for loop testing, instrument maintenance and valve set-up, with an easy to read display and simple to use time saving features.

# UPS III IS Druck Loop Calibrator


UPS III IS is a Druck product. Druck has joined other GE high-technology sensing businesses under a new name—GE Industrial, Sensing.



# GE Sensing

## Graphic Display

The graphic display with menu-driven interface is easier to use than traditional knobs, switches, multi-function keys and dual key sequences.



## Measure or Source 0 to 24 mA


An internal loop supply is available in both measure and source modes, essential during plant shutdowns.

## Accuracy 0.015% of Reading

This includes 12 month stability and temperature effects. The UPS III IS can maintain a 4:1 calibration ratio with the latest instrumentation and is typically 10 to 40 times more accurate than a Digital Multi-Meter (DMM).

## Simultaneous % Readout

Displays mA and the percentage value of 4 to 20 mA or 0 to 20 mA. The UPS III IS also converts mA readings to % flow. This is not possible with many loop calibrators.



## Step, Span Check and Value Check

Step quickly through linearity tests and zero/span adjustments. In valve mode, seating can be checked and the actuator set.

Step Mode	0%	25%	50%	75%	100%
4 to 20 mA linear	4	8	12	16	20
0 to 20 mA linear	0	5	10	15	20
4 to 20 mA flow	4	5	8	13	20
0 to 20 mA flow	0	1.25	5	11.25	20
4 to 20 mA span check	4	–	–	–	20
0 to 20 mA span check	0	–	–	–	20
4 to 20 mA valve	3.8, 4, 4.2	–	12	–	19, 20, 21

## Auto Step and Ramp

Outputs have adjustable rates (1 to 599 s) for single-handed loop testing, valve set-up and slew rate checks.

## “Fast Set” Output

Allows values to be set to within 0.001 mA using the arrow keys. Holding a key quickly ramps the output to the next value. The system is ideal for alarm trip tests.

## 50 VDC Measurement

For loop diagnostics and maintenance of voltage output instruments.

## Continuity and Switch Test Facility

This reduces DMM dependence when fault finding, checking loop integrity and testing switches.

## Hart® Compatible

Internal 220 Ω loop resistor (menu selectable)

## EMC compliance to EN 61326-1

Complies with heavy industry standard. Most loop calibrators are only suitable for light industrial use.

## Other Features

- Adjustable display contrast
- Adjustable resolution
- Uses industry standard AA batteries
- Battery voltage and battery low indicator
- Information screen reports serial number, software version and calibration date
- Primary reading in mA or %
- Auto power off (enable or disable)
- Pin protected closed case calibration
- Leather case with carry strap (Note: the UPS III IS must be used in the case for hazardous area use)

# UPS III IS Specifications

## Performance

Function	Range	Resolution	1 year Accuracy <sup>1</sup> % rdg + counts	Remarks
Source mA	24 mA	0.001	0.015% + 2	V-max 30 V
Source mA and 21V	24 mA	0.001	0.015% + 2	R-max 650 Ω at 20 mA
Measure mA	24 mA	0.001	0.015% + 2	V-max 30 V
Measure mA and 21V	24 mA	0.001	0.015% + 2	R <sub>measure</sub> 15 Ω
Measure V	50 V	0.001	0.015% + 4	R <sub>measure</sub> 1 M Ω
Continuity	< 100 Ω			0.5 mA current

<sup>1</sup>Accuracy includes temperature effects 62°F to 80°F (17°C to 27°C). For use outside these limits add 0.015%/°F (0.003%/°C).

## Electrical

### Power Supply

4 x 1.5 V AA-size alkaline batteries (see certificate for type)

### Battery Life

60 hours in measure mode, 14 hours at 12 mA

### Auto Power Down

30 minutes after last key press

### Low Battery Warning

Battery symbol displayed

### Open Loop

Flashes "open loop"

### Loop Resistance High

Flashes "check loop Ω"

### Out of Range

Displays <<<< (under), >>>> (over)

### Hart Resistor

220 Ω menu selectable loop resistor



## Environmental

### Calibration Reference

72°F (22°C) ±2°F(±3.6°C)/RH 45% ±15%

### Operating Temperature

14°F to 104°F (-10°C to 40°C)

### Relative Humidity

0% to 90% non-condensing

### Conformity

EN 61010, EN 61326-1:1997 + A1 (1998) + A2 (2001) + A3 (2003), CE marked

Certified for use in hazardous areas

ATEX: II 2G Ex ib IIC T4 (-10°C ≤ T<sub>a</sub> ≤ +40°C)

Certificate number Baseefa 06ATEX0224X

IEC: Ex ib IIC T4 (-10°C ≤ T<sub>a</sub> ≤ +40°C)

Certificate number IECEx BAS 06.0053X

## Physical

### Housing Material

High impact ABS

### Dimensions (w x h x d)

3.5 in x 5.5 in x 1.7 in (90 mm x 140 mm x 42 mm)

### Weight

16.2 oz (460 g) including batteries and leather case

### Display

Graphic LCD, 1.2 in x 2.1 in (31 mm x 54 mm)

### Electrical Terminals

Gold plated, 4 mm sockets

# UPS III IS Specifications

## Supplied As Standard

The UPS III IS is supplied as standard with leather case and carry strap, a certificate of calibration, user guide, test leads, and a set of alkaline batteries.

## Calibration Standards

Instruments manufactured by GE are calibrated against precision equipment traceable to International Standards.

## Related Products

### **Portable Field Calibrators**

A comprehensive range of portable pressure, temperature and electrical field calibrators

### **Laboratory and Workshop Instruments**

A comprehensive range of pressure indicators and controllers. Also included are pressure measurements industrial deadweight testers and GE Ruska high precision controllers and primary standard piston gauges.

### **Pressure Transducers and Transmitters**

A wide range of pressure transducers and transmitters including analog, digital and Hart/Smart devices. Please contact GE for further information.

## Ordering Information

### **Please state the following:**

- Model—UPS III IS



©2006 GE. All rights reserved.  
920-374A\_E

All specifications are subject to change for product improvement without notice. GE® is a registered trademark of General Electric Co. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.