

Part No.

# NPAK-4FBA-RG-2m-1m

Nitropak, 1/2" female BSPP gauge adapter, 2 hoses, 2 process connections

Self contained nitrogen source includes all connections and hoses to connect directly to a pressure gauge or calibrator

## Features

- Proprietary pressure balanced fine adjustment piston allows for extremely precise, finger-tip control of pressure at 0.03 psi (2 mbar) or 3000 psi (210 bar) or any range in between.
- Easily refillable nitrogen cylinder holds enough gas for multiple calibrations
- Nylon bag to hold hose and fittings attached to inside of lid
- Includes storage compartment in control panel for pressure reference test gauge
- Low volume Quick-test hose, gauge adapter and process connection can be attached to NPAK without thread sealant or a wrench
- Optional padded strap for field use (NPAK-STRP)
- Made in U.S.A.

## Item Includes

- Assembly - NPAK Assembly (NPAK)
- Gauge Adapter - G 1/2" female BSPP (ISO 228/1) x female QT, no check-valve, brass (QTHA-4FBA-RG)
- Hose - Quick-test hose, brass hose ends, 2 m (6.6 ft) long (QTQT-HOS-2m)
- Hose - Quick-test hose, brass hose ends, 1 m (3.3 ft) long (QTQT-HOS-1m)
- Hose Adapter - G 1/4" female BSPP (ISO 228/1) x male QT, no check-valve, brass (QTHA-2FB0-RG)
- Hose Adapter - G 1/4" female BSPP (ISO 228/1) x male QT, no check-valve, brass (QTHA-2FB0-RG)

## Specifications

|                   |  |
|-------------------|--|
| Pressure Range    | 0 to 3000 psi (0 to 207 bar)   |
| Vacuum Range      | 0 to 10"Hg (0 to 254 mmHG)   |
| Temperature range | 0 to 130 °F (-18 to 54 °C)   |
| Construction      | ABS Plastic, Aluminum, Anodized Aluminum, Brass, Plated Steel, Stainless Steel, Zippered Nylon with Velcro |
| Seal materials    | Buna-N, Delrin, Teflon   |



NPAK-4FBA-RG-2m-1m