

Part No.

# DPOV-2MBA

*DPOV pump, 1/4" male NPT gauge adapter, hose, process connection*

Perform very precise low pressure calibration or differential pressure calibration using an attached gauge or calibrator (gauge and calibrator not included)

## Features

- Light weight, compact pump generates up to 100 psi (7 bar) with ease
- Large volume fine adjustment piston provides precise control, even at very low pressures
- Modular design makes field maintenance quick and easy
- Precisely vent pressure with soft seated bleed valve
- Two outlet ports provide connections for both pressure reference and for device under test thus eliminating a tee
- Low volume Quick-test hose, gauge adapter and process connection can be attached to pump without thread sealant or a wrench
- Rugged, all metal construction reduces pressure changes due to temperature fluctuations
- Made in U.S.A.

## Item Includes

- Hand Pump - DPOV Assembly (DPOV)
- Gauge Adapter - 1/4" male NPT x male female QT, no check-valve, brass (QTHA-2MBA)
- Hose - Quick-test hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Hose Adapter - 1/4" male NPT x male QT, no check-valve, brass (QTHA-2MB0)

## Specifications

|                        |  |
|------------------------|--|
| Pressure Range         | 0 to 100 psi (0 to 7 bar)  |
| Media                  | Air  |
| Outlet Port1           | Male Quick-test, brass   |
| Outlet Port2           | Male Quick-test with cap and chain, brass                              |
| Temperature Range      | 0 to 130 °F (-18 to 54 °C)   |
| Construction           | Anodized Aluminum, Brass, Stainless Steel                              |
| Seal Materials         | Buna-N, Delrin, Teflon   |
| Fine Adjust Resolution | ±0.01 psi  |
| Weight                 | 1.6 lb (0.7 kg)  |
| Dimensions             | H: 2.88 in (7.3152 cm) x W: 7.93 in (20.1422 cm) x D: 3.5 in (8.89 cm) |



DPOV-2MBA